

Specifications CS-H6c-R101-1G2WF

Camera

Image Sensor	F2.4 @ 1/3" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
IR Night Vision Distance	Up to 10 m (33 ft)
Lens	4 mm, viewing angle: 85° (Diagonal), 75° (Horizontal), 45° (Vertical)
Lens Mount	M12
DNR	3D DNR
WDR	Digital WDR
Day & Night Switch	IR-cut filter with auto-switching

Video & Audio

Max. Resolution	1080p, 1920 × 1080
Frame Rate	Max. 15 fps; Self-Adaptive during network transmission
Video Compression	H.264
Video Bit Rate	Adaptive bit rate.

Storage

Local Storage	Supports microSD card (Up to 256 GB)
Cloud Storage	Supports EZVIZ CloudPlay storage (subscription required)

Network

Wi-Fi Standard	IEEE 802.11 b, 802.11 g, 802.11 n
Frequency Range	2.4 ~ 2.4835 GHz
Channel Bandwidth	Supports 20 MHz
Security	64 / 128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK
Transmission Rate	11b 11 Mbps, 11g 54 Mbps, 11n: 72 Mbps
Wi-Fi Pairing	AP paring
Protocol	EZVIZ Cloud Proprietary Protocol
Interface Protocol	EZVIZ Cloud Proprietary Protocol
Wired Network	RJ45 × 1 (10M / 100M Adaptive Ethernet Port)

General

Dimensions	88 × 88.2 × 119 mm (3.46 × 3.47 × 4.69 in)
Packaging	103 × 103 × 186 mm (4.06 × 4.06 × 7.30 in)
Net Weight	218 g (7.69 oz)
Operating Conditions	-10° to 45° C (14° to 113° F) Humidity 95% or less (non-condensing)

Power

Power Supply	DC 5V / 1A
Power Consumption	Max. 5 W